



# Casting Optimization and Robust Design Considering Composition Uncertainties of Secondary Alloys in the Horizon Europe Project RecAL

**International MAGMA User Meeting 2024  
Frankfurt, October 10, 2024**

**Alberto Vergnano and Hamed Rezvanpour  
University of Modena and Reggio Emilia**



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

# RecAL - Recycling Technologies for Aluminium

Horizon Europe  
CL4-2023-Twin-  
Transition-01-42



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

## PROJECT FACTS

- HEU Research and Innovation Action project call CL4-2024-TT-01-42
- Total budget of **10.9 M€**
- **48 months** from **01.01.2024**
- **Leichtmetallkompetenzzentrum Ranshofen** – Austrian Institute of Technology leads consortium of 19 partners




## PROJECT OBJECTIVES

- **Digital circularity platform (HUB)** for the entire aluminum recycling value chain
- Optimize **scrap purity** by advanced **sorting and refining** technologies
- Maximizing the **impurity tolerance** of next-generation alloy designs
- Data for **CO<sub>2</sub> footprint** and **product passport** via blockchain



# Global AL flows in 2030



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

S. Van den Eynde et al.: "Forecasting global aluminium flows to demonstrate the need for improved sorting and recycling methods", Waste Management, 137, 2022, <https://doi.org/10.1016/j.wasman.2021.11.019>

# Project Consortium

19 Partners  
8 EU Countries  
+ UK




Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.





# RecAL CATs

- CATs 'Circular Amplification Technologies' for up- and recycling technologies




Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

Adapted from K-Businesscom AG, April 2023 <https://www.k-business.com/ueber-uns/open-circularity-platform>

# Cluster A - HUB and Interface

- **Digital cockpit** that will connect the 14 CATs.
- **RecAL Hub connects suppliers with buyers.**
- **Circular processing chain**, from design to scrapping to manufactures demands.
- **Anonymised data sharing architecture** to secure the marketplace.



RecAL Hub schematic with stakeholders and outputs



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

# Clusters B\* - Melt Refinement, Salt Slag Upcycling and Sorting Automation

Compressed aluminum scrap, © shutterstock




- **CAT 1. Melt refinement by salt**
  - Improve yield and refining capacity of new upgraded types of Al-scrap
- **CAT 2. Salt slag refinement**
  - Upcycle hazardous salt slag residue generated when aluminium scrap is melted
- **CAT 3. Robotics for sorting**
  - Robots with more flexibility to sort a wider range of scrap sizes and shapes
- **CAT 4. AI for Sorting**
  - AI feedback loop for melted material data to enable self-regulating process
- **CAT 5. Robotic Dismantling**
  - Robots equipped with artificial vision cameras to dismantle rivets from fuselage



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

# Cluster C - Formulas

- **CAT 6. Formula 6xxx Wrought**
  - A hybrid 6xxx-alloy with widened composition range for improved recyclability
- **CAT 7. Formula Physical Properties**
  - Conductor alloys for automotive cable applications from 6xxx to 1xxx scrap
- **CAT 8. Formula 7xxx Wrought**
  - 8-12% aviation and scrap from 5&6xxx (from CAT 5) to reach 50% scrap rate
- **CAT 9. Formula High Tolerance AM**
  - High-strength Al alloy for AM, based on the aeronautic scrap/improved recyclability
- **CAT 10. Formular Casting Nano & A226**
  - Advance circularity potential of future cast aluminium alloys from H2020 SUSTAINair




Microstructure of as-cast alloy based on the AlSiMg system with additions of Fe, Mn and Cu reflecting relevant EoL scrap contents. Above: backscattered electron image, below: optical micrograph ©LKR





Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.




# Cluster D - Paradigm Shift



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.




# Types of Alloying compositions



**1- The main elements** are the additives that control the mechanical properties and castability (Si, Mg, Cu, Zn, Mn, Li)

**2- The secondary elements** are mainly used for solidification behavior control, microstructural and grain refinement (Ti, Sr, Zr, B, V, Sc, Cr)

**3- Impurities** are unwanted elements that should be controlled or eliminated (Fe, Na, Ca)



# Robustness Assessment in the Optimization of LPDC Subject to Variations in Secondary Alloy Composition


CAD design

Casting  
Simulation

Process  
parameter  
optimization

Sensitivity  
analysis



Final design  
ranking





# CAD design and Casting simulation in MAGMA

## CAD design details




Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

Casting simulation  
using MAGMA

# Why porosity occurs?

- The porosity occurs because of the non-sequential solidification phenomena
- It can be controlled by controlling solidification stage parameters



shrinkage porosity occurrence (a) before the separation; (b) after the separation




Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

# Optimization parameters


## Objective:

- Minimizing porosity to Less than 5%



## Control factors

HTC Category	Parameter levels	Number of levels
1- COOLING CHANNEL UP	500 - 2500 W/m <sup>2</sup> K (step size = 500)	5
2- COOLING CHANNEL SURFACE EXT	100 - 900 W/m <sup>2</sup> K (step size = 200)	5
3- COOLING CHANNEL SURFACE INT	0.001- 400 W/m <sup>2</sup> K (step size = 100)	5
4- COOLING CHANNEL DOWN	500 - 2500 W/m <sup>2</sup> K (step size = 500)	5
5- COOLING CHANNEL DOWN INT	2200 - 3000 W/m <sup>2</sup> K (step size = 200)	5
POURING TEMPERATURE	700 - 740 (step size = 10)	5



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

# Genetic Algorithm optimization



- The total search space is  $5^6 = 15625$
- The optimization runs for 10 generations
- The initial population size is 16

$$NIP = N_{obj} \times N_{dv} \times 2 \begin{cases} \text{If } N < 16 & N_{IP} = 16 \\ \text{If } N > 16 & N_{IP} = N \end{cases}$$

Rank	Design	Up_ext	Surf_ext	Down_intern	Down	Up	Surf_int	Down_center	Up_in	Surf_up_in	Initial Temperature
1	147	1800	900	3000	1500	1900	300	2500	2800	300	720
2	160	2300	1000	3000	2100	1900	300	2300	2800	200	730
3	149	1000	700	3000	1500	1900	300	2500	2800	200	720
4	152	200	700	3000	1400	2000	200	2500	1000	200	720
5	146	200	900	3000	1500	2200	200	2500	2800	200	720
6	107	200	700	3000	1500	1900	300	2500	2800	200	720



in & Cooling until Eject, Porosity



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.



# S/N ratio calculation and QL function

*Signal to Noise ratio calculation:*

**Nominal is better:**

$$SN_n = -10 \log[(Y_0 - \mu)^2 + \sigma^2] \quad (1)$$

**Higher is better:**

$$SN_l = -10 \log \left[ \frac{1}{n} \sum_{i=1}^n \frac{1}{\{(y)_i\}^2} \right] \quad (2)$$

**lower is better:**

$$SN_s = -10 \log \left[ \frac{1}{n} \sum_{i=1}^n \{(y)_i\}^2 \right] \quad (3)$$

**Quality Loss function:**


$$QL = L(Y) = K[Y - Y_0]^2 = (\mu - Y_0)^2 + \sigma^2 \quad (4)$$

Fe	Si	Cr	Zn
0.5	7	0	0.1
0.5	7.25	0.075	0.15
0.5	7.5	0.15	0.2
0.65	7	0.075	0.2
0.65	7.25	0.15	0.1
0.65	7.5	0	0.15
0.8	7	0.15	0.15
0.8	7.25	0	0.2
0.8	7.5	0.075	0.1



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

# DOSE S/N and QL analysis




Design	Mean	Standard Deviation	Variance	Quality Loss	S/N Ratio
Design 1	1.391	3.934	15.479	17.414	-12.409
Design 2	0.989	2.797	7.823	8.801	-9.44538
Design 3	2.664	4.406	19.413	26.512	-14.2344
Design 4	5.613	9.273	85.325	116.834	-20.6757
Design 5	2.262	2.399	5.756	10.871	-10.3627
Design 6	1.967	2.939	8.637	12.504	-10.9706
Design 7	2.701	3.209	10.299	17.592	-12.4531
Design 8	2.009	3.936	15.491	19.527	-12.9064
Design 9	2.411	2.188	4.787	10.597	-10.252
Design 10	8.621	8.492	72.114	146.438	-21.6565

Material	Fe	Sr	Cr	Zn
Levels				
1	-5.929	-10.445	-4.798	-8.94
2	-17.662	-12.84	-14.15	-14.103
3	-12.843	-13.148	-17.485	-13.391
Delta	11.733	2.702	12.686	5.163
Rank	2	4	1	3



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

# DOSE S/N and QL analysis



S/N ratio analysis for alloying compositions

Linear graph in QL function, (a) mean values; (b) QL function



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.

# Conclusions

With RecAL:



**Increased impurity tolerance in alloy design without compromising performance**



**Harmonising communication between all sectors of the aluminium industry**



**Creating recycle streams with vastly enhanced impurities**



**Adapting production to unlock potential of secondary resources**



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.



# Thank you!

Alberto Vergnano  
UniMoRe  
WP Cluster D Leader

Hamed Rezvanpour  
UniMoRe  
CAT 13 Researcher



[recal-project.eu](http://recal-project.eu)



[@RecAL\\_Project](https://twitter.com/RecAL_Project)



[linkedin.com/showcase/recal-eu](https://linkedin.com/showcase/recal-eu)



**UNIMORE**  
UNIVERSITÀ DEGLI STUDI DI  
MODENA E REGGIO EMILIA



Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or REA. Neither the European Union nor the granting authority can be held responsible for them.