

International MAGMA User Meeting 2024

October 9-11, 2024

RADISSON BLU – Frankfurt

BE
PART
OF
IT

Using a Neural Network with MAGMASOFT® Optimization Data

Selecting optimum conditions for the HPDC process

Fredrik Cooper (MSc Eng)

Pietermaritzburg, South Africa



PDC - South Africa



- Innovative, non-ferrous foundry supplying the automotive (tier 1 and tier 2 supplier), electrical transmission and building sectors, locally and internationally.
- Operating for 72 years from Pietermaritzburg, South Africa.
- Several 280t to 630t high pressure die castings machines, with material alloying capability.
- In-house tool development, simulation, manufacturing and maintenance.
- ISO 9001, 14001 and IATF accredited.
- PDC is focussed on finding technically accurate solutions in a cost-effective way and implementing them to be practical and robust.

Project objectives

- Keep existing tooling and cavity layout
- Reduce rejects in critical volumes of casting
- Determine
 - causes for rejects
 - process parameters for optimum settings

PDC propriety content removed

PDC propriety content removed

Geometry changes

- Biscuit size
- Gate area
- Runner area
- Gate entry angle
- Overflow size
- Overflow ingate area
- Temper channel depth

Process changes

- Times
- Temperatures
- Positions
- Velocities
- Pressures

ID1

ID2

ID3

- 14 variables:
 - Allowed die design changes
 - All process related changes done in past trials
- 10 results:
 - Quality objectives in the casting
 - Process limitations of the HPDC cell
- 9.3 trillion possible designs

AIMS:

Investigate effects of HPDC process variables and allowed die design variations

Evaluation Areas ID2 and ID3 require zero porosity/entrapment



4 core license constraint



- 7

Neural Network

- All variables and results are considered simultaneously.
- Trained with data exported from Optimization Perspective.
- The NN is an estimation of the model space simulated.



- Interactive manipulation of variables and dynamic visualization of all results simultaneously.
- Higher design resolution can be achieved because more setting steps can be applied.
- All possible designs and many more can be assessed without further simulation.


The NN required unbiased data of the whole design space for training – no Magmasoft optimization methods were used.

- 1 generation Sobol – 200 designs.
- Objectives applied to Air and Porosity only.
- Constraints used as data capture of relevant quality and process information.

Project statistics

- 60 hours (4 core license)
- 186 designs calculated
- 14 design errors

186 designs were used for training the NN



Neural Network - User Meeting Demo

Reset to Default

Build Optimizing Conditions DONE

INPUTS

Minimum Maximum 0.017

STEP

Pouring Temperature:		600 C	<input type="text" value="60"/>
Shot Delay:		8 sec	<input type="text" value="4"/>
1st stage velocity:		0.1 m/s	<input type="text" value="0.25"/>
Trigger Position:		320 mm	<input type="text" value="80"/>
2nd stage velocity:		1.5 m/s	<input type="text" value="1.75"/>
Biscuit Length:		100 mm	<input type="text" value="35"/>
Intensification Pressure:		650 bar	<input type="text" value="250"/>
Die Oil Temperature:		125 C	<input type="text" value="62"/>
Die Oil Channel Depth:		40 mm	<input type="text" value="5"/>
Gate Thickness:		4 mm	<input type="text" value="1"/>
Runner/Gate Area Ratio:		1.5	<input type="text" value="0.3"/>
Gate Entry Angle:		0 deg.	<input type="text" value="20"/>
Overflow Ingate Thickness:		3 mm	<input type="text" value="1"/>
Overflow Radius:		10 mm	<input type="text" value="2.5"/>

OUTPUTS

score: 0.017

MSD of Air and Porosity

Air:		0.012 mm ³
Porosity:		0.021 mm ³
Air - ID2:		0.012 mm ³
Air - ID3:		0.039 mm ³
Porosity - ID3:		0.002 mm ³
Air - shot sleeve/biscuit:		0.398 mm ³
Temperature - Cavity Filling:		574 C
Fraction Liquid - Cavity Filling:		64 %
Velocity Ratio - Gates:		0.1
Velocity Ratio - 2nd stage:		0.1

Neural Network - User Meeting Demo

[Reset to Default](#)

[Build Optimizing Conditions](#) from 6.059115208473127e+21 designs (< 3M to build optimizing conditions)

INPUTS

Minimum Maximum 0.020

STEP













Pouring Temperature:		620 C	<input type="text" value="1"/>
Shot Delay:		6.0 sec	<input type="text" value="0.1"/>
1st stage velocity:		0.15 m/s	<input type="text" value="0.05"/>
Trigger Position:		220 mm	<input type="text" value="1"/>
2nd stage velocity:		3.0 m/s	<input type="text" value="0.1"/>
Biscuit Length:		80 mm	<input type="text" value="1"/>
Intensification Pressure:		650.0 bar	<input type="text" value="10"/>
Die Oil Temperature:		175 C	<input type="text" value="1"/>
Die Oil Channel Depth:		45 mm	<input type="text" value="1"/>
Gate Thickness:		4.0 mm	<input type="text" value="0.1"/>
Runner/Gate Area Ratio:		1.5	<input type="text" value="0.1"/>
Gate Entry Angle:		20 deg.	<input type="text" value="1"/>
Overflow Ingate Thickness:		3.0 mm	<input type="text" value="0.1"/>
Overflow Radius:		9.2 mm	<input type="text" value="0.1"/>

OUTPUTS

score: 0.045

Air:		0.024 mm^3
Porosity:		0.059 mm^3
Air - ID2:		0.021 mm^3
Air - ID3:		0.080 mm^3
Porosity - ID3:		0.113 mm^3
Air - shot sleeve/biscuit:		0.283 mm^3
Temperature - Cavity Filling:		574 C
Fraction Liquid - Cavity Filling:		86 %
Velocity Ratio - Gates:		0.6
Velocity Ratio - 2nd stage:		0.6

Neural Network optimum results compared with training dataset

	Rank	Design	Air (-)	Porosity (-)	
	Rank 1	(1) Version 2/d1	0.00912	0.0	Minimum Optimum
	Rank 2	Design 10	0.0107	0.0262	
	Rank 3	Design 30	0.00741	0.0339	
	Rank 4	Design 2	0.0121	0.0448	
	Rank 5	Design 167	0.0144	0.0445	
	Rank 6	Design 82	0.0325	0.0331	
	Rank 7	(2) Version 2/d2	0.021	0.0448	Practical Optimum
	Rank 8	Design 55	0.0843	0.0187	
	Rank 9	Design 83	0.0261	0.0745	
	Rank 10	Design 133	0.0101	0.0873	
	Rank 11	Design 63	0.0189	0.0961	
	Rank 12	Design 37	0.0331	0.088	

Air Entrapment

Minimum optimum

Practical optimum

PDC propriety content removed

Shrinkage Porosity

Minimum optimum

Practical optimum

PDC propriety content removed

- Porosity result bars had most movement with following variables:
 - 1st stage velocity,
 - trigger position,
 - shot delay,
 - pouring temperature,
- The rejects visible in real world castings were therefore primarily Shrinkage Porosity, then secondly Air Entrapment.
- Overflow size had some influence on improving Air Entrapment.
- Gate thickness had some influence on improving Shrinkage Porosity.

- Lowest Air and Porosity levels were discovered with the NN method.
- A Practical Optimum was established and its impact could be assessed.
- Causes of rejects were determined and the influence of geometric parameters established.
- Large order of design possibilities were assessed with a 4-core license.

Thank You for your attention

Demonstration Neural Network available at:

<https://www.modelit.co.za/projects/UserMeeting/>

Fredrik Cooper (MSc Eng)
fredc@modelit.co.za
www.modelit.co.za